


TO-131



MILLIMETER DIMENSIONS ARE DERIVED FROM ORIGINAL INCH DIMENSIONS

SYMBOL	INCHES		MILLIMETERS		NOTES
	MIN.	MAX.	MIN.	MAX.	
A	.145	.185	3.69	4.69	1
B	.028	.032	.712	.812	2
C	.014	.016	.356	.406	2
ϕD	.355	.375	9.02	9.52	1
ϕD_1	.270	.285	6.86	7.23	-
L	.450	.550	11.5	13.9	2,3
L_1	-	.035	-	.88	2,7
Q	.055	-	1.40	-	-
Q_1	.005	.020	.13	.50	-

NOTES:

1. BODY CONTOUR OPTIONAL WITHIN ϕD AND A. ϕD MIN APPLIES TO GREATEST BODY DIAMETER.
2. TYPICAL ALL LEADS.
3. OMISSION OF ONE LEAD OPTIONAL. THE NUMBER AND POSITION OF LEADS ACTUALLY PRESENT ARE INDICATED IN THE PRODUCT REGISTRATIONS.
4. LEAD 4 END CONFIGURATION OPTIONAL.
5. INDEX MARK TO BE VISIBLE FROM TOP.
6. INDEX MARK OPTIONAL FOR THREE-LEAD DEVICES.
7. LEAD DIMENSIONS NOT CONTROLLED IN THIS ZONE TO ALLOW FOR BODY AND LEAD FINISH IRREGULARITIES.

ITEM NO. 238 G

JEDEC PUBLICATION 95 REGISTERED OUTLINES FOR SEMICONDUCTOR DEVICES	OUTLINE TO-131	ISSUE A	DATE JULY 1968