


Flanged double-ended ceramic package; 2 mounting holes; 4 leads

SOT268A



DIMENSIONS (millimetre dimensions are derived from the original inch dimensions)

| UNIT | A | b | c | D | E | e | F | H | H ₁ | p | Q | q | U ₁ | U ₂ | w ₁ | w ₂ | w ₃ |
|--------|----------------|----------------|----------------|----------------|----------------|-------|----------------|----------------|----------------|----------------|----------------|-------|----------------|----------------|----------------|----------------|----------------|
| mm | 4.91 4.19 | 1.66 1.39 | 0.13 0.07 | 12.96 12.44 | 6.48 6.22 | 6.45 | 2.04 1.77 | 17.02 16.00 | 8.23 7.72 | 3.43 3.17 | 2.67 2.41 | 18.42 | 24.90 24.63 | 6.61 6.35 | 0.25 | 0.51 | 0.25 |
| inches | 0.193 0.165 | 0.065 0.055 | 0.005 0.003 | 0.510 0.490 | 0.255 0.245 | 0.254 | 0.080 0.070 | 0.670 0.630 | 0.324 0.304 | 0.135 0.125 | 0.105 0.095 | 0.725 | 0.980 0.970 | 0.260 0.250 | 0.010 | 0.020 | 0.010 |

| OUTLINE VERSION | REFERENCES | | | | EUROPEAN PROJECTION | ISSUE DATE |
|--------------------|------------|-------|------|--|------------------------|------------|
| | IEC | JEDEC | EIAJ | | | |
| SOT268A | | | | | | 99-03-29 |