





Earless Flanged ceramic package; 2 leads

SOT1227B



Dimensions

Unit ⁽¹⁾	A	b	c	D	D ₁	E	E ₁	F	H	Q	U ₁	U ₂	w ₁	w ₂
mm	max 3.68	1.40	0.15	5.18	5.21	4.17	4.19	1.07	8.64	1.70	5.21	4.19	0.25	0.380
	nom 2.84	1.14	0.08	4.98	4.95	3.96	3.94	0.97	7.62	1.45	4.95	3.94		
	min 0.145	0.055	0.006	0.204	0.205	0.164	0.165	0.042	0.340	0.067	0.205	0.165	0.01	0.015
inches	max 0.145	0.055	0.006	0.204	0.205	0.164	0.165	0.042	0.340	0.067	0.205	0.165	0.01	0.015
	nom 0.112	0.045	0.003	0.196	0.195	0.156	0.155	0.038	0.300	0.057	0.195	0.155		
	min 0.112	0.045	0.003	0.196	0.195	0.156	0.155	0.038	0.300	0.057	0.195	0.155		

Note

1. Millimeter dimensions are derived from the original inch dimensions.

sot1227b_po

Outline version	References				European projection	Issue date
	IEC	JEDEC	JEITA			
SOT1227B						12-06-08 13-10-15