


Flanged ceramic package; 2 mounting holes; 2 leads

SOT1227A



Dimensions

Unit ⁽¹⁾	A	b	c	D	D ₁	E	E ₁	F	H	p	Q	q	U ₁	U ₂	w ₁	w ₂
mm	max 3.68	1.40	0.15	5.18	5.21	4.17	4.19	1.14	8.64	2.67	1.70		14.10	4.19		
	nom 2.84	1.14	0.08	4.98	4.95	3.96	3.94	0.89	7.62	2.41	1.45	9.53	13.84	3.94	0.25	0.380
	min 2.84	1.14	0.08	4.98	4.95	3.96	3.94	0.89	7.62	2.41	1.45	9.53	13.84	3.94	0.25	0.380
inches	max 0.145	0.055	0.006	0.204	0.205	0.164	0.165	0.045	0.340	0.105	0.067		0.555	0.165		
	nom 0.112	0.045	0.003	0.196	0.195	0.156	0.155	0.035	0.300	0.095	0.057	0.375	0.545	0.155	0.01	0.015
	min 0.112	0.045	0.003	0.196	0.195	0.156	0.155	0.035	0.300	0.095	0.057	0.375	0.545	0.155	0.01	0.015

Note

1. Millimeter dimensions are derived from the original inch dimensions.

sot1227a_po

Outline version	References				European projection	Issue date
	IEC	JEDEC	JEITA			
SOT1227A						12-06-08 13-10-14