


NOTES :



1. REFER TO APPLICABLE SYMBOL LIST.
2. DIMENSIONING AND TOLERANCING PER ANSI Y14.5, 1973.
3. FIGURE 2 APPLICABLE TO VARIATION AA.
4. FIGURE 1 APPLICABLE TO VARIATION AB AND AC.
5. BODY CONTOUR OPTIONAL WITHIN ϕD AND A.
6. LEAD DIMENSIONS UNCONTROLLED IN THIS ZONE TO ALLOW FOR BODY AND LEAD IRREGULARITIES.
7. TYPICAL ALL LEADS.
8. OMISSION OF ONE LEAD OPTIONAL.
9. LEAD NO. 4 END CONFIGURATION OPTIONAL.
10. MEASURED FROM INTERSECTION OF LEAD AXIS AND BODY SURFACE OF ϕD_1 .
11. CONTROLLING DIMENSIONS: INCH.

SYMBOL	VARIATIONS (ALL DIMENSIONS SHOWN IN INCHES)												
	AA		NOTE	AB		NOTE	AC		NOTE	MIN.	MAX.	NOTE	
	MIN.	MAX.		MIN.	MAX.		MIN.	MAX.					
A	.145	.200		.170	.180	5	.145	.185	5				
b	.035	.046	7	.028	.032	7	.028	.032	7				
c	.012	.019	7	.014	.016	7	.014	.016	7				
ØD	.593	.680	5	.400	.455	5	.355	.375	5				
ØD ₁	.520	.680	10	.320	.330		.270	.285					
ØD ₂	.480	-		-			-	-					
L	.195	-	10	.475	.525		.450	.550					
L ₁	-	.105	6	-	.035	6	-	.035	6				
Q	.005	.020	5	.055	-		.055	-					
Q ₁	-	-		.005	.020		.005	.020					
NOTE	1,2,3,8,11			1,2,4,8,11			2,2,4,8,11						
REF.	TO-121			TO-130			TO-131						
ISSUE	A Jan. 1976			A Jan. 1976			A Jan. 1976			A Jan. 1976			
JEDEC SOLID STATE PRODUCT OUTLINES				TITLE DISC FAMILY PERIPHERAL LEADS				ISSUE A		DATE 1/20/76		TO-227 VARIATION AA THRU AC	