



Flanged hermetic ceramic package; 2 mounting holes; 2 leads

SOT445A



DIMENSIONS (mm are the original dimensions)

UNIT	A	b	c	D	D <sub>1</sub>	D <sub>2</sub>	E	E <sub>1</sub>	E <sub>2</sub>	F	H	p	Q	q	U <sub>1</sub>	U <sub>2</sub>	w <sub>1</sub>	w <sub>2</sub>
mm	4.01 3.36	3.15 2.95	0.15 0.09	7.9 7.7	7.65 7.35	8.15 7.85	4.1 3.9	4.25 3.95	5.31 5.01	1.67 1.37	15.84 14.64	3.35 3.05	3.33 3.03	14.22	20.47 20.17	5.18 4.98	0.30	0.51
inches	0.158 0.132	0.125 0.115	0.006 0.003	0.312 0.303	0.302 0.289	0.321 0.309	0.162 0.153	0.168 0.155	0.210 0.197	0.066 0.054	0.624 0.576	0.132 0.120	0.132 0.119	0.56	0.806 0.794	0.204 0.196	0.012	0.020

OUTLINE VERSION	REFERENCES				EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	EIAJ			
SOT445A						99-03-29